

Title: Polycrystalline photovoltaic panel parameters 50w

Generated on: 2026-04-10 15:27:28

Copyright (C) 2026 ALEXANDRA BESS. All rights reserved.

---

This document provides specifications for a 50W poly-crystalline solar module. The module has 36 cells, dimensions of 156mm x 156mm, a maximum power output of 50W, an open circuit voltage of 21.6V, ...

Applications Any large or small on-grid /off-grid solar power stations. Commercial/industrial building roof-top and ground systems. Residential roof-top and ground systems.

50P-BP Solartech J-Series Modules Solartech photovoltaic J-Series Modules are constructed with high efficient polycrystalline solar cells and produce higher output p. r module than others in it class. This ...

ARACTERISTICS Max. Power (W) 50 Efficiency (%) 14 Max. Power Voltage, Vmp (V) 17.60 Max. Power Current, Imp (A) Open Cir.

Our polycrystalline PV panels 50W/55W give you a reliable product at an attractive price point. They're easier to stock and ship than larger panels but still provide meaningful power output. You will ...

Technical parameter Maximum Power(W) 50W Optimum Power Voltage(Vmp) 18.43V Optimum Operating Current(Imp) 2.71A Open Circuit Voltage(Voc) 22.48V Short Circuit Current(Isc) 2.98A ...

KF Solar Tech Group Corp. is a professional manufacturer and supplier of high performance 50w polycrystalline solar panels.

Exceptional low-light performance and high sensitivity to light across the entire solar spectrum. 25-Year limited warranty on power output and performance. 5-Year limited warranty on materials and ...

Website: <https://lesfablesdalexandra.fr>

